

Best/Flex Roller

Gravity Applications

Excellent for handling odd shaped boxes, bags and low grade cartons.

Move in and out of trucks with POWERTRAX for faster, safer, easier loading and unloading. See page 5.



- 220 kg capacity per linear metre (level)
- 762 to 1080 mm adjustable conveyor height
- 450, 600 and 750 mm conveyor widths
- Available in any length to fit your applications

The above conveyor is equipped with an optional package stop that drops down when not needed.

SPECIFICATIONS

	Model Number	Standard Lengths Compacted to Expanded	Leg Sets Per Unit	Roller Axle Centres (Extended)	Approx. Shipping Weight
450mm WIDTHS	B/FR-18-12	1.2m - 3.7m	4	127mm	102 kg
	B/FR-18-16	1.6m - 4.9m	5	127mm	132 kg
	B/FR-18-20	2.0m - 6.1m	6	127mm	163 kg
	B/FR-18-24	2.4m - 7.3m	7	127mm	193 kg
600mm WIDTHS	B/FR-24-12	1.2m - 3.7m	4	127mm	109 kg
	B/FR-24-16	1.6m - 4.9m	5	127mm	138 kg
	B/FR-24-20	2.0m - 6.1m	6	127mm	170 kg
	B/FR-24-24	2.4m - 7.3m	7	127mm	200 kg
750mm WIDTHS	B/FR-30-12	1.2m - 3.7m	4	127mm	116 kg
	B/FR-30-16	1.6m - 4.9m	5	127mm	145 kg
	B/FR-30-20	2.0m - 6.1m	6	127mm	177 kg
	B/FR-30-24	2.4m - 7.3m	7	127mm	206 kg

Adjustable Height: Standard adjustable range is from 720mm to 1.08metres. 150mm castor option adds 23mm to conveyor height to make adjustable range from 785mm to 1.1013metres. 200mm castor option adds 90mm to conveyor height to make adjustable range from 850mm to 1.2metres.

Axle Centres: When expanded, the distance between axle centres is 127mm. Optional 76mm and 100mm axle centres are available. Optional axle centres affect compacted conveyor length. Call our Sales Team for assistance.

Extended Lengths: BEST/FLEX Gravity Roller conveyors are available in any length. If your application requires a length not listed in the above chart, call our Sales Team for assistance.

FEATURES

- **Self Tracking**—Cartons follow the twists and turns of the conveyor path without using engineered curves.
- **Adjustable Height**—Simply turn the locking knob to raise or lower the conveyor bed height.
- **Square Tubing Legs**—LongReach offers heavy duty square tubing legs for longer service life.
- **38mm Side Plates**—Aluminium alloy construction features a ribbed design for added durability. Assembled with bolts and lock nuts.
- **Castors with brakes**—Colson 127mm x 38mm swivel castors roll easily. Castor brakes lock both wheel and swivel simultaneously while the conveyor is in use.

PERFORMANCE OPTIONS



Package Stop.
Stops cartons at the end of the conveyor and drops down when not needed.



Side Rails.
Prevents cartons from skewing off the conveyor in accumulation applications.



Leg Connect Brackets.
Easily connects two or more conveyors to span greater distances.



Axle Centres.
Optional 76mm and 102mm axle centres are available for small package applications.



Colson 150mm x 50mm Swivel Castors.
For easier rolling over uneven surfaces. Adds 23mm to conveyor height.